AMENDMENTS TO THE CLAIMS

The following claims are given merely for ease of reference. ***No amendments are introduced.***

Claims:

1.   (Previously Presented) A system to monitor the level of light in an area comprising:

at least one sensor that measures the level of light in a lighted area;

at least one transceiver that communicates information regarding the level of light in the lighted area, via a communications network, the transceiver configured to repeat messages received from other transceivers associated with other sensors;

a central system that communicates with the transceiver via the communications network; and

a network that allows access to the central system.

2.   (Original) The system of claim 1 wherein the lighted area is one selected from the group consisting of a parking structure, a building, a residence, an underground facility, and a street.

3.   (Original) The system of claim 1 wherein a sensor is one selected from a group consisting of a light sensor, and a camera sensor.

4.   (Original) The system of claim 1 wherein the central system comprises of a memory and a processor.

5.   (Original) The system of claim 1 wherein the communications network comprises of a Public Service Telephone Network.

6.   (Previously Presented) The system of claim 1 wherein the communications network communicates with a second communications network via a gateway.

7.   (Original) The system of claim 1 wherein a central processing unit and a memory communicates with the sensor and the transceiver.

8.   (Original) The system of claim 7 wherein the transceiver communicates information with a transceiver in another lighted area, wherein the communication between the transceivers form an RF cloud.

9.   (Original) The system of claim 1, wherein a person who is a technician or a customer, can access the central system.

10.   (Previously Presented) The system of claim 1, wherein the network is selected from a group comprising the Internet, a wide-area network, and a local-area network.

11.   (Original) The system of claim 8, wherein the RF cloud forms a backbone that allows a transceiver in a remote lighted area to communicate with the central system via the communications network.

12.   (Canceled)

13.   (Previously Presented) A computer program for monitoring the level of light in an area, the computer program being embodied on a computer readable medium, the computer program comprising:
        a first logic, the first logic sensing the level of light in a lighted area;
        a second logic, the second logic communicating the level of light in the lighted area, via a communications network, to a central system;
        a third logic, the third logic accessing the central system via a network; and
        a fourth logic for receiving a message from a transceiver and repeating the message.

14. – 16. (Canceled)

17. (Previously Presented) A system to monitor the level of light in an area comprising:

a sensor that measures the level of light in an lighted area; and

a transceiver that communicates the level of light in the lighted area received from the sensor to a central system and repeats messages received from other transceivers associated with other sensors.